Standard Workstations

Standard Series

Model: _____

Item #: _____ Quantity: _____

Project: _____

1800 or 2100 Series Available
(see reverse)

- **Drainboard:**
  20 gauge 304 series stainless steel.
- **Dump Sink:**
  20 gauge 304 series stainless steel 10" x 14" x 6" deep with 1 1/2" drain located in center.
- **Blender Shelf:**
  22 gauge 304 series stainless steel.
- **Interior:**
  20 gauge 304 series stainless steel.
- **Cold Plate:**
  Cast aluminum post mix plate with seven circuits. Plate is sealed into bottom. Each circuit is 5/16" OD stainless steel tubing. Two full with remainder to be half circuits. Bump and swedge fittings on ends.
- **Front Apron:**
  22 gauge 304 series stainless steel clad over 20 gauge galvaneal.
- **Backsplash:**
  22 gauge 304 series stainless steel clad over 20 gauge galvaneal.
- **Sides, Back and Bottom:**
  20 gauge galvaneal.
- **Legs:**
  1 5/8" tubular 16 gauge galvanized steel with grey plastic bullet foot.
- **Electrical (blender):**
  Duplex outlet located underneath.
- **Faucet:**
  4" center wall or deck mount.
- **Plumbing:**
  1/2" IPS hot and cold water
  1" IPS drain connection w/o cold plate
  1/2" IPS drain connection w/ cold plate.
  1" IPS drain connection (drainboard).
  1 1/2" IPS drain connection (dump sink).

Accessories

- ☐ Standard Single Tier Keyhole Speedrail (available sizes: 24", 30", 36", and 48")
- ☐ Standard Double Tier Keyhole Speedrail (available sizes: 24", 30", 36", and 48")
- ☐ Upgrade to Eight Circuit Cold Plate
- ☐ Stainless Steel Divider (specify Ice Bin model)
- ☐ Perforated Bottom (units w/o Cold Plates)
- ☐ Stainless steel Sliding Cover (specify Ice Bin model and if bottle holders are being used)
- ☐ Condiment Tray
- ☐ Perforated Dump Box
- ☐ Additional Accessories (see Accessory Sheet)

Approved By: _____

Krowne Metal Corporation
257 Verona Ave. Newark, New Jersey 07104
www.krowne.com **sales@krowne.com**

Phone: 800-631-0442
FAX: 973-485-1424

Krowne

Standard Workstations

Model: _____ Item #: _____Quantity: _____ Project: _____

1800 Series





Model Numbers	Overall Length (A)	Ice Bin Length & Depth (B)	Drainboard Length (C)	Blender/ Dump Length (D)	Ice Bin Location	Blender Location	Cold Plate Circuits	Weight lbs
18-W42L	3'-6"	24"/12"	n/a	18"	left	right	n/a	75
18-W42R	3'-6"	24"/12"	n/a	18"	right	left	n/a	75
18-W48L	4'-0"	30"/12"	n/a	18"	left	right	n/a	82
18-W48R	4'-0"	30"/12"	n/a	18"	right	left	n/a	82
18-W54L	4'-6"	36"/12"	n/a	18"	left	right	n/a	92
18-W54R	4'-6"	36"/12"	n/a	18"	right	left	n/a	92
18-W42L-7	3'-6"	24"/12"	n/a	18"	left	right	7	110
18-W42R-7	3'-6"	24"/12"	n/a	18"	right	left	7	110
18-W48L-7	4'-0"	30"/12"	n/a	18"	left	right	7	117
18-W48R-7	4'-0"	30"/12"	n/a	18"	right	left	7	117
18-W54L-7	4'-6"	36"/12"	n/a	18"	left	right	7	127
18-W54R-7	4'-6"	36"/12"	n/a	18"	right	left	7	127
18-W66L	5'-6"	24"/12"	24"	18"	center	left	n/a	125
18-W66R	5'-6"	24"/12"	24"	18"	center	right	n/a	125
18-W66L-7	5'-6"	24"/12"	24"	18"	center	left	7	230
18-W66R-7	5'-6"	24"/12"	24"	18"	center	right	7	230
18-D48L	4'-0"	24"/8"	24"	n/a	left	n/a	n/a	65
18-D48R	4'-0"	24"/8"	24"	n/a	right	n/a	n/a	65
18-D60L	5'-0"	24"/8"	36"	n/a	left	n/a	n/a	75
18-D60R	5'-0"	24"/8"	36"	n/a	right	n/a	n/a	75
18-D48L-7	4'-0"	24"/8"	24"	n/a	left	n/a	7	100
18-D48R-7	4'-0"	24"/8"	24"	n/a	right	n/a	7	100
18-D60L-7	5'-0"	24"/8"	36"	n/a	left	n/a	7	120
18-D60R-7	5'-0"	24"/8"	36"	n/a	right	n/a	7	120

2100 Series





Model Numbers	Overall Length (A)	Ice Bin Length & Depth (B)	Drainboard Length (C)	Blender/ Dump Length (D)	Ice Bin Location	Blender Location	Cold Plate Circuits	Weight lbs
21-W42L	3'-6"	24"/12"	n/a	18"	left	right	n/a	90
21-W42R	3'-6"	24"/12"	n/a	18"	right	left	n/a	90
21-W48L	4'-0"	30"/12"	n/a	18"	left	right	n/a	97
21-W48R	4'-0"	30"/12"	n/a	18"	right	left	n/a	97
21-W54L	4'-6"	36"/12"	n/a	18"	left	right	n/a	105
21-W54R	4'-6"	36"/12"	n/a	18"	right	left	n/a	105
21-W42L-7	3'-6"	24"/12"	n/a	18"	left	right	7	125
21-W42R-7	3'-6"	24"/12"	n/a	18"	right	left	7	125
21-W48L-7	4'-0"	30"/12"	n/a	18"	left	right	7	132
21-W48R-7	4'-0"	30"/12"	n/a	18"	right	left	7	132
21-W54L-7	4'-6"	36"/12"	n/a	18"	left	right	7	140
21-W54R-7	4'-6"	36"/12"	n/a	18"	right	left	7	140
21-W66L	5'-6"	24"/12"	24"	18"	center	left	n/a	125
21-W66R	5'-6"	24"/12"	24"	18"	center	right	n/a	125
21-W66L-7	5'-6"	24"/12"	24"	18"	center	left	7	230
21-W66R-7	5'-6"	24"/12"	24"	18"	center	right	7	230
21-D48L	4'-0"	24"/8"	24"	n/a	left	n/a	n/a	90
21-D48R	4'-0"	24"/8"	24"	n/a	right	n/a	n/a	90
21-D60L	5'-0"	24"/8"	36"	n/a	left	n/a	n/a	100
21-D60R	5'-0"	24"/8"	36"	n/a	right	n/a	n/a	100
21-D48L-7	4'-0"	24"/8"	24"	n/a	left	n/a	7	125
21-D48R-7	4'-0"	24"/8"	24"	n/a	right	n/a	7	125
21-D60L-7	5'-0"	24"/8"	36"	n/a	left	n/a	7	145
21-D60R-7	5'-0"	24"/8"	36"	n/a	right	n/a	7	145

Mechanical Requirements:

- 1/2" IPS hot and cold water
- 1/2" IPS drain connection (Cold Plate)
- 1" IPS drain connection
- 1 1/2" IPS drain connection (Dump Sink)

Approved By: _____

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Krowne Metal Corporation
257 Verona Ave. Newark, New Jersey 07104
www.krowne.com sales@krowne.com

Phone: 800-631-0442
FAX: 973-485-1424

02/05