

S-SERIES RESTAURANT RANGE

S24E - 4 Open Burners, Space Saver Oven **S24C -** 4 Open Burners, Cabinet Base



(S24E shown)









Southbend is a leader in the commercial cooking industry. Since 1898 Southbend has been dedicated to providing the highest quality and most innovative cooking equipment to customers in all facets of the food service industry. Customers choose Southbend due to the reliable performance, endless versatility and pricing value of the equipment. Southbend products are engineered to perform and built to last.

STANDARD EXTERIOR FEATURES

- 24-1/4" wide open top with four (4) 28,000 BTU NAT (24,000 BTU LP) PATENTED, one-piece cast iron, non-clog burners with Lifetime Warranty.
- Stainless steel front, sides and removable shelf.
- 4" Stainless steel front rail with closed, welded end caps.
- Four (4) removable, cast iron grate tops (rear holds up to 14" stock pot).
- Removable, one-piece crumb drawer under burners.
- Metal knobs w/ red stripe.
- Hinged, lower valve panel.
- Quadrant spring doors with heat resistant, ergonomic, chrome handle.
- 6" stainless steel, adjustable legs.
- Factory installed pressure regulator.


SPACE SAVER OVEN FEATURES (E)


- 35,000 BTU space saver oven with snap action thermostat adjustable for 250°F to 550°F.
- U-shaped heavy duty oven burner.
- Equipped with flame failure safety device.
- Large 19-1/2" wide X 26-1/2" deep oven with all oven cavity parts enameled.
- Four sides and top of oven insulated with heavy, self-supporting block type rock wool with oven baffle assembly.
- 2-position rack guides with one removable rack.


CABINET BASE FEATURES (C)


Aluminized cabinet with removable, stainless steel doors that open from the center.











Dimensions - in(mm)

Model	Exterior									Соок Тор	Door Opening	OVEN BOTTOM	3/4" Gas Conn.		
	Width A	Depth B	С	D	Е	F	G	Н	J	К	L	М	N	0	Р
S24E	24.25" (616)	34.00" (864)	29.75" (756)	31.00" (787)	12.00° (305)	2.75" (70)	59.50" (1511)	22.50° (572)	31.00" (787)	6.00" (152)	37.00" (940)	15.50" (394)	13.00" (330)	2.50" (64)	30.25" (768)
S24C	24.25" (616)	34.00" (864)	29.75" (756)	31.00" (787)	12.00" (305)	2.75" (70)	59.50" (1511)	22.50" (572)	31.00" (787)	6.00" (152)	37.00" (940)	10.50" (267)	-	2.50" (64)	30.25" (768)

Model		OVEN INTERIOR		Crate Size			Cubic	CRATED	
WIODEL	WIDTH	Dертн	Неіднт	WIDTH	Dертн	Неіднт	Volume	WEIGHT	
S24E	19.50" (495)	26.50" (673)	14.00" (356)	44.00" (1118)	45.50" (1158)	48.00" (1219)	55.6 cu. ft 1.58 cu.m.	350 lbs. 158.8 kg.	
S24C	-	-	-	44.00" (1118)	45.50" (1158)	48.00" (1219)	55.6 cu. ft 1.58 cu.m.	350 lbs. 158.8 kg.	

UTILITY INFORMATION

0	BURNERS (BTU/EACH)						
Gas Type	OPEN TOP BURNER	SPACE SAVER OVEN					
Natural	28K	35K					
LP	24K	35K					

- Each unit has a 3/4", male, rear gas connection.
- Minimum inlet pressure Natural Gas is 4" W.C
 - Propane Gas is 11" W.C.
- Check local codes for fire, installation and sanitary regulations.
- For installation on combustible floors and adjacent to combustible walls, allow 6" clearance.
- If using Flex-Hose, the I.D. should not be smaller than the I.D. of the manifold of the unit to which it is being connected.
- If casters are used, a restraining device should be used to eliminate undue strain on the flex hose.
- Install under vented hood.
- If the unit is connected directly to the outside flue, an A.G.A approved down draft diverter must be installed at the flue outlet of the oven.

BIDDING SPECIFICATIONS

The unit shall be a 24-1/4" wide, S-Series Restaurant Range with four (4) 28,000 BTU NAT (24,000 BTU LP) open top burners with four (4) removable cast iron grate tops. The exterior of the unit shall be constructed of stainless steel and have a 4" stainless steel front rail with closed, welded end caps. The unit shall have 6" stainless steel, adjustable legs. The unit shall come with a 22.5" high stainless steel flue riser with single shelf. The unit shall come with a factory installed regulator.

E - The unit shall have a 35,000 BTU space saver oven with snap action thermostat, adjustable from 250° F to 550° F. The interior shall be enameled on both sides and measure 19-1/2" wide X 26.5" deep X 14" high, and includes 2-position rack guides with one removable rack.

C - The unit shall have an aluminized cabinet base with removable, stainless steel doors that open from the center.

OPTIONS AND ACCESSORIES

- Casters all swivel front with locks П
- 10" flue riser
- 3/4" quick disconnect with flexible hose complies
 - with ANSI Z 21.69 (Specify 3ft, 4ft or 5ft)

- Restraining device П
- Step up burners
- Extra oven racks
- Auxiliary griddle plates
- Solid rail or cutouts
- Cutting board
- 24" cheesemelter mounted
 - to flue

NOTICE:

Southbend has a policy of continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

INTENDED FOR COMMERCIAL USE ONLY. NOT FOR HOUSEHOLD USE.



1100 Old Honeycutt Road, Fuguay-Varina, NC 27526 Phone: (919)-762-1000 • Fax: (800)-910-9915 • URL: www.southbendnc.com