



# BEVERAGE-AIR

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

### **Commercial Refrigeration Equipment General Specification**

#### CABINET CONSTRUCTION

- Exterior—Stainless steel exterior.
- Interior—Stainless steel interior.
- Insulation—2" foamed-in-place CFC and HCFC-free polyurethane insulation.
- Separate top mount evaporator housing in 2 & 3 section models.
- Freezer section in 2 & 3 section models is located at right sec-
- Single section model includes top half refrigerator, bottom half freezer with evaporators mounted to ceiling.
- Non-electric condensate evaporation is provided at the exterior top of 2 & 3 section models.
- Heated condensate evaporation is provided at the bottom of sinale section cabinet.

#### **DIGITAL THERMOMETER**

 Exterior digital thermometer provides a digital display of cabinet temperatures.

#### REFRIGERATION SYSTEM

- Top mount, environmentally friendly refrigeration systems. Refrigerators maintain product temperatures of 36°-38°F. Freezers maintain product temperatures at 0°F.
- Refrigerators utilize R134a & freezers R404A refrigerant, which are (CFC and HCFC-free) for compliance with environmental safety standards.

#### **DOORS**

- Solid and Half-Solid door configuration.
- Anti-microbial door handles and door locks are standard.
- Field reversible doors and cam lift hinges standard. Positive seal self-closing door(s) with 120° stay open feature.
- · Snap-in door gaskets of one piece construction, removable without tools for ease of cleaning.
- Three (3) heavy duty epoxy coated wire shelves per section standard. Four (4) shelf clips included per shelf (field installed).
- Shelves are adjustable in ½" increments.

## **MODEL FEATURES**

- · Incandescent interior lighting.
- 6" heavy-duty legs included. 3" or 6" casters are optional.
- UL-EPH and CUL for open food product.



**SOLID & HALF-SOLID DOORS** 

MODELS: PRF24-24-1AS-02 PRF48-24-1AS-02

PRF12-12-1HS-02 PRF24-24-1AHS-02 PRF48-24-1AHS-02













\*Note: Not all markings may apply to all model variations

Available From:


Model Specified	Store#
Location	Quantity




# **Top Mount, Dual Temperature Reach-In's** Models: PRF12, PRF24, PRF48

MODEL	PRF24-24-1AS-02 SOLID DOOR	PRF48-24-1AS-02 SOLID DOOR	PRF12-12-1HS-02 HALF-SOLID	PRF24-24-1AHS-02 HALF-SOLID	PRF48-24-1AHS-02 HALF-SOLID
EXTERNAL DIMENSIONAL DATA					
Length Overall (inches) Length Overall (mm)	52" 1321	78" 1981	26" 660	52" 1321	78" 1981
Depth Overall—(inches) less handle Depth Overall—(mm) less handle	30" 762	30" 762	33" 838	33" 838	33" 838
Height Overall— (inches) less legs Height Overall— (mm) less legs	78 1/2" 1994	78 1/2" 1994	78 1/2" 1994	78 1/2" 1994	78 1/2" 1994
INTERNAL DIMENSIONAL DATA					
NET Capacity (cubic ft.) NET Capacity (Liters)	23.1 / 23.1 654 / 654	46.6 / 23.1 1320 / 654	9.1 / 9.1 258 / 258	23.1 / 23.1 654 / 654	46.6 / 23.1 1320 / 654
Number of Shelves	6	9	4	6	9
ELECTRICAL DATA					
Full Load Amperes 115/60/1	5.7—6.0	9.4—10.6	4.5—7.5	5.7—6.0	9.4—10.6
REFRIGERATION DATA					
Horsepower	1/4—1/2	1/3—1/2	1/4—1/3	1/4—1/2	1/3—1/2
WEIGHT DATA					
Gross Weight (Crated lbs)	701	580	438	705	1020
Gross Weight (Crated kg)	318	263	199	320	463

# **PLAN VIEWS**



PRF12-12-1HS



PRF24-24-1AHS









Note: Not all markings may apply to all model variations.

