Metalfrio | Solutions

REACH IN UPRIGHTS
REFRIGERATORS and FREEZERS

Mdl CFD3RR-72
Mdl CFD3FF-72

FEATURES

- Stainless steel series 430 exterior doors, fronts & sides
- Stainless steel series 304 interior doors, sides & flooring
- Stucco aluminum back panel
- Recessed handle on front of door
- Self closing hinged doors with 90°stay open feature
- LED digital temperature display
- Interior lighting
- PVC coated adjustable steel shelves
- Safety door lock and keys
- Automatic defrost by thermostat cycle
- Removable door gasket to allow cleaning
- Forced air system with manual temp control
- Temperature range / refrigerator: 32° to 50°F
- Temperature range / freezer: 0 to -10°F
- Standard 5" industrial casters / front locking
- Optional 6" legs
- Thick 2.5" foamed in place polyurethane insulation
- 8-ft power cord and plug set

SPECIFICATIONS

Model	Doors/ Shelves	External Dimensions W x D x H	Gross Cu Ft	Shipping Weight	Amps	H/P	CFC-free Refrigerant	Electrical
CFD3RR-72	3 / 9	81.0" x 32.2" x 82.5"	75.0	700	10-1/2	3/4	R-134a	115/120V, 60Hz
CFD3FF-72	3 / 9	81.0" x 32.2" x 82.5"	75.0	708	14	1-1/2	R-404a	115/120V, 60Hz

Internal Dimensions







CFD3RR-72
CFD3FF-72



NEMA 5-15P

WARRANTY
18 Months Parts and Labor
5 Years Compressor (part only)

Administered by:
Metalfrio Solutions
(888) 403-0070 Toll Free

Certified to ANSI/NSF 7 Standards

Product design and specifications are subject to modification by manufacturer without prior notice.

Metalfrio Solutions, Inc.
110 Enterprise Parkway - Boerne, TX 78006
(888) 403-0070 Toll Free - (888) 339-1904 Toll Free Fax
www.metalfrio.com - sales@metalfrio.com

Effective Date - January, 2011