☑ Electrolux

2 Drawer Refrigerated-Freezer Base 48"

••=•••	
MODEL #	
PROJECT NAME #	-
SIS #	_
AIA#	



EM Series

2 Drawer Refrigerated-Freezer Base 48"

727093 (COMP48)

2 DRAWER REFRIGERATED-FREEZER BASE 48" (1218 mm)

Short Form Specification

Item No.

Unit to be Electrolux Two (2) Drawer Refrigerated/Freezer Base with built-in compressor unit. Unit able to oprate both as refrigerator or as freezer, with temperature range from -7.6°F to +46.4°F (-22°C to +8°C). Digital thermostat and display are protected by the Stainless Steel front panel. Stainless Steel front panel with incorporated Stainless Steel wire netting is easy to remove for access to the thermostat and to allow for easy cleaning. May be installed below any top unit. Perforated top surface provides the necessary ventilation to allow for a flush connection between base and Electrolux top units, eliminating the need for the top unit legs. Each drawer to accommodate two (2) 12" x 20" x 6" deep pans with use of included, removable division bar or two (2) 325 mm x 530 mm (1/1 GN) pans. Drawer guides with safety stop can support up to 264 lbs. (120 kg) and are removable for cleaning. Magnetic snap-in drawer gaskets are removable for cleaning. Perforated bottom plate in each drawer guarantees correct air-flow, allows for small pans to stand upright and is removable for cleaning. Perforated bottom plate can support up to 88 lbs. (40 kg). Forced air circulation for rapid cooling and an even temperature distribution. Access to all components from the front and bottom. CFC free (ecological refrigerant type: R404a, - gas in foam: cyclopenthane). Suitable for use in ambient temperatures of up to 104 °F (40 °C). Rounded corners inside well for safe and easy cleaning. Constructed entirely in AISI 304 Stainless Steel with Scotch Brite finish, Right-angled side edges to allow flush fitting joints between units, minimizing gaps and possible dirt traps, Heavy duty Stainless Steel tubular drawer $handles.\ Supplied\ with\ 6" (150\ mm)\ height\ adjustable,\ removable\ legs.\ Unit\ may\ be\ installed\ on\ castors.$





Main Features

- Two (2) Drawer Refrigerated/Freezer Base with built-in compressor unit.
- Unit able to operate both as refrigerator or as freezer, with temperature range from -7.6°F to +46.4°F (-22°C to +8°C).
- Digital thermostat and display are protected by the Stainless Steel front panel.
- Stainless Steel front panel with incorporated Stainless Steel wire netting is easy to remove for access to the thermostat and to allow for easy cleaning.
- May be installed below any top unit.
- Perforated top surface provides the necessary ventilation to allow for a flush connection between base and Electrolux top units, eliminating the need for the top unit legs.
- Each drawer to accommodate two (2) 12" x 20" x 6" deep pans with use of included, removable division bar or two (2) 325 mm x 530 mm (1/1 GN) pans.
- Drawer guides with safety stop can support up to 264 lbs. (120 kg) and are removable for cleaning.
- · Magnetic snap-in drawer gaskets are removable for cleaning.
- Perforated bottom plate in each drawer guarantees correct air-flow, allows for small pans to stand upright and is removable for cleaning.
- Perforated bottom plate can support up to 88 lbs. (40 kg).
- Forced air circulation for rapid cooling and an even temperature distribution.
- Access to all components from the front and bottom.
- CFC free (ecological refrigerant type: R404a, gas in foam: cyclopenthane).
- Suitable for use in ambient temperatures of up to 104 °F (40 °C).
- Rounded corners inside well for safe and easy cleaning.
- Constructed entirely in AISI 304 Stainless Steel with Scotch Brite finish.
- Right-angled side edges to allow flush fitting joints between units, minimizing gaps and possible dirt traps.
- Heavy duty Stainless Steel tubular drawer handles.
- Supplied with 6" (150 mm) height adjustable, removable legs.
- Unit may be installed on castors.

Optional Accessories

4 swivelling castors kit for refrigerator/freezer bases - 2 with brakes

Approval:

EM Series 2 Drawer Refrigerated-Freezer Base

Front V 677 [26§"] 150 [5⁷."] ΕI 90.5 [39"] 1036.5 [4013"] 90.5 [3<mark>9</mark>"] Top 1217.5 [4715"] TCA 1396 [54拾"] Electrical connection Equipotential screw Side 811.7 [32"] 739.2 [29"] EI 546 [21<mark>7</mark>"]

89.2 [3¹/₇"]

Electric

Supply voltage:

727093(COMP48) 120 V/1N ph/60 Hz

12 Amps: **Total Watts:** 1.15 kW

Key Information

External dimensions, Width 47 15/16" (1218 mm) External dimensions, Depth 32 1/64" (813 mm) External dimensions, Height 26 3/4" (680 mm) Net weight: 260 lbs (118 kg) Shipping width: 33 7/16" (850 mm) Shipping depth: 50 13/16" (1290 kg) Shipping height: 30 11/16" (780 mm) **Shipping weight:** 276 lbs (125 kg) **Shipping volume:** 30.2 ft3 (0.86 m3) Refrigerant weight: 0.375 lbs (170 kg)

Refrigeration Data

Compressor power: 1/2 hp, self-contained

Refrigerant type: R404a 1958 W Refrigeration power:

EM Series 2 Drawer Refrigerated-Freezer Base 48"

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.