P.O. Box 248



# ADVANTEDGETM REFRIGERATED CHEF BASE

www.norlake.com



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

.....

## SPECIFICATIONS FOR: NLCB53, NLCB71, NLCB83, NLCB96

Stainless steel interior front, sides, rear and heavy-duty marine edge top. Galvanized bottom Finish: and back.

Insulation: The complete cabinet and drawers are foamed in place with polyurethane insulation.

Electrical: 115 volt, 60 Hz, 1 phase with cord and NEMA 5-15P Plug.

Hardware: Heavy-duty stainless steel drawers supported on stainless steel telescoping drawer slides

with stainless steel roller bearing wheels. Drawer units intended to withstand minimum of 200 lbs. Full marine edge top to prevent spills from flowing over edge. Heavy-duty 4" casters.

Drawers include pan adapter bars for full-size pans (pans not included).

Refrigeration: Self-contained refrigeration system utilizes R134a refrigerant metered by a capillary tube

system. Automatic condensate evaporator. Interior forced air system with high humidity evaporator coils. Adjustable temperature control. Temperature range 32°F to 40°F. Digital

temperature indicator.

UL, C-UL and ETL Sanitation listed Approvals:

### STANDARD FEATURES

- Adjustable temperature control
- Automatic condensate evaporator
- Capillary tube system
- Digital temperature indicator
- Full marine edge top
- Full size pan adapter bars (pans not included)
- 4" casters consuming 5"
- Stainless steel exterior finish
- Stainless steel interior finish

#### Stainless steel drawers

- Temperature range: 32°F to 40°F
- UL, C-UL and ETL Sanitation
- Warranties: 1 year parts & labor, 5 year compressor

#### OPTIONAL FEATURES


Legs






TOP NLCB71

1790 [70 1/2]




FRONT NLCB71

2115 [83 1/4]




TOP NLCB83

2115 [83 1/4]




FRONT NLCB83

2440 [96 1/16]





TOP NLCB96

2440 [96 1/16]



FRONT NLCB96





**FRONT** 


TOP

NLCB53

			SPECIFICATIONS	
Model	NLCB53	NLCB71	NLCB83	NLCB96
Crated Weight (lbs.)	230	340	355	390
Interior Height	16-1/2"	16-1/2"	16-1/2"	16-1/2"
Interior Width	39-3/4"	57-1/2"	70-1/2"	83-1/2"
Interior Depth	21-3/4"	21-3/4"	21-3/4"	21-3/4"
Overall Height	25-1/2"	25-1/2"	25-1/2"	25-1/2"
Overall Width	53"	70-1/2"	83-1/4"	96-1/6"
Overall Depth	30-1/2"	30-1/2"	30-1/2"	30-1/2"
Gross Cubage (ft.3)	9.8	14.3	17.2	21.4
Full Size Pan Capacity**	6	8	10	12
Number of Drawers	2	4	4	4
Condensing Unit Size	1/5 HP	1/5 HP	3/8 HP	3/8 HP
Refrigerant	R-134a	R-134a	R-134a	R-134a
Electrical Characteristics	115/60/1	115/60/1	115/60/1	115/60/1
Cord and Plug Furnished	Yes	Yes	Yes	Yes
Nema Plug Configuration	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	3.3	3.3	6.0	6.0

Specifications subject to change without notice.

<sup>\*\*</sup> Pans not included.









Revision Date: 12/11 © 2011 NOR-LAKE, INC. Printed in the U.S.A. Part Number: 143582