

## GF Series - Reach In Hinged Glass Doors Freezer - Top Mount

• PRODUCT SPECIFICATIONS SHEETS



Shown is a bottom mount freezer

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Self-Contained Remote	GF22 R-GF22	GF48 R-GF48	GF75 R-GF75	GF102 R-GF102
Length	26-1/2"	52-1/4"	78"	103-3/4"
Height with casters	83"	83"	83"	83"
Depth with drain cover (Dimensions are +/-1/4")	36-1/2"	36-1/2"	36-1/2"	36-1/2"

- Specification subject to change without notice

## GF Series - Reach In Hinged Glass Doors Freezer - Top Mount

### Standard Specifications and Optional Features

<p><b>CONSTRUCTION</b>          UL Classified to ANSI/NSF 7          Heavy duty construction          CFC free foamed in place insulation          Removable front grille for easy servicing          1, 2, 3 or 4 door models available          Heavy duty edge mounted hinges</p>	<p><b>FINISHES</b>          Doors-Anthony style 101-chrome finish          Exterior-designer white          Interior-designer white          Rear-designer white</p>
<p><b>INTERIOR</b>          White aluminum ends and back          White aluminum floor          Aluminum evaporator fan housing          4 Heavy duty epoxy coated shelves per door</p>	<p><b>REFRIGERATION</b>          Top mounted condensing unit          R404A refrigeration          1, 2, 3, &amp; 4 door-expansion valve          Electric condensate pan          Remote available</p>
<p><b>EXTERIOR</b>          White aluminum ends and fronts          Triple pane glass doors 23-3/4"X62-1/4"  <i>(provides wide view display)</i>          Externally mounted dial thermometer          5" Casters</p>	<p><b>LIGHTING</b>          Vertical light behind mullion          1 Dr = 1 light          2 Dr = 1 light          3 Dr = 2 lights          4 Dr = 3 lights</p>
<p><b>ELECTRICAL REQUIREMENTS</b>          115V/208-230V/60Hz/1Ph          Unit must be hard wired          UL/CUL listed</p>	<p><b><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></b></p> <p><b><i>Important Note: Product must be cooled before being displayed within the case.</i></b></p>

### OPTIONAL FEATURES

<p>Stainless steel, laminate, or paint          Digital thermometer          Door swing change</p>	<p>Extra shelf with clips          Door locks          6" legs (black or stainless steel top mount units only)</p>
--	--



## GF Series - Reach In Hinged Glass Doors Freezer - Top Mount

### Technical Data

Model	Self contained	GF22	GF48	GF75	GF102
	Remote	R-GF22	R-GF48	R-GF75	R-GF102
<b>Length</b> <b>Height with casters</b> <b>Depth with drain cover</b> <b>(Dimensions are +/- 1/4")</b>		26-1/2" 83" 36-1/2"	52-1/4" 83" 36-1/2 "	78" 83" 36-1/2 "	103-3/4" 83" 33-7/8"
<b>Operating temperature</b> <b>Refrigerant (expansion valve)</b> <b>Compressor size- HP</b> <b>Temperature control setting</b> <b>@ 75F at 55%</b>	Self contained Self contained	-10°F to 0°F R404A 3/4	-10°F to 0°F R404A 1-1/2	-10°F to 0°F R404A 1-3/4	-10°F to 0°F R404A (2) 1-1/2
<b>Defrost per day (24 hours)</b> <b>BTU's at -35°F Evap. Temp.</b> <b>Voltage</b> <b>Amperage</b> <b>Amperage</b> <b>Cord and plug</b>	CUT IN CUT OUT Electric Remote Self contained Remote	30 10 3 @ 30 min. 2160 115/208-230V 11.8A N/A No	30 10 3 @ 30 min. 4060 115/208-230V 4.2/11.0A 5.6/6.5A No	30 10 3 @ 30 min. 5150 115/208-230V 5.2/11.8A 7.4/8.6A No	30 10 3 @ 30 min. 8120 115/208-230V 8.3/11.0A 10.4/6.5A No
<b>Exterior color</b> <b>Interior color</b> <b>Inside end panels</b> <b>Floors</b> <b>Drain Electric Condensate</b> <b>Total shelves</b> <b>Door size</b> <b>Cubic capacity (ft<sup>3</sup>)</b>		White White White White Yes 4 23-3/4"X62-1/4" 22	White White White White Yes 8 23-3/4"X62-1/4" 48	White White White White Yes 12 23-3/4"X62-1/4" 75	White White White White Yes 16 23-3/4"X62-1/4" 102

### SHIPPING INFORMATION

<b>Height</b>		86"	86"	86"	82"
<b>Depth</b>		44"	44"	44"	44"
<b>Length</b>		31"	58"	84"	109"
<b>Gross weight</b>	Self contained Remote	390# 240#	590# 440#	790# 650#	1174# 874#
<b>Cubic feet</b>		73ft <sup>3</sup>	118ft <sup>3</sup>	171ft <sup>3</sup>	223ft <sup>3</sup>

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice

## GF Series - Reach In Hinged Glass Doors Freezer - Top Mount

### Technical Data • Side View • Plan View

