



BEVERAGE-AIR

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

Commercial Refrigeration Equipment General Specification

WTRD SERIES—29" DEPTH

Versatile, compact (29" depth) with stainless steel work tops and 4" high removable backsplash for refrigerated storage of food products. Working height is 35 1/2".

CABINET CONSTRUCTION

Heavy duty construction includes exterior stainless steel on front, sides, door(s) and grille. Cabinet back and bottom are galvanized steel. Interior liner is made of corrosion resistant anodized aluminum. Interior thermometer is standard.

In cabinets with doors and drawers, doors are mounted to face of cabinet on cartridge-style hinges permitting them to self close under their own weight. Hinges also allow doors to stay open 120° and permit easy door removal for service and cleaning if required. A plug-in type vinyl magnetic gasket is attached to each door for positive seal.

Cabinet insulation is CFC and HCFC-free foamed-in-place polyurethane of two-inch minimum thickness. Units are supplied with 6" high casters. Front casters have wheel locking mechanism.

DRAWER CONSTRUCTION

Drawer frames are constructed of heavy-duty stainless steel. Telescoping design slides make opening drawers smooth and easy. Heavy duty construction ensures maximum support of stored food products. Slides have locking mechanism to prevent drawers from being pulled off of cabinets. For your convenience, drawers accommodate 6" or 4" deep pans. Heavy-duty pan divider supports are supplied. Foodservice pans for drawers are not included. Snap-type vinyl magnetic gasket is attached to each drawer for positive seal. Drawers extend 17" (when opened).

REFRIGERATION

Robust and balanced refrigeration system ensures that food stays fresh for a longer period of time. Optimum air flow inside cabinets helps in keeping uniform temperature within the cabinet. Refrigeration system uses environment friendly R134a refrigerant which is CFC and HCFCfree. Design utilizes automatic condensate removal process.

ELECTRICAL

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.

ELECTRICAL CONNECTION

Units pre-wired at factory and include 8' long NEMA-5-15P cord and plug



*Note: Not all markings may apply to all model variations.

WORKTOP REFRIGERATORS WITH DRAWERS WTRD 29" DEPTH SERIES MODELS: WTRD27A WTRD48A WTRD60A WTRD72A



Available From:

Model Specified

Store#

Location

Quantity


BEVERAGE-AIR


Undercounter Refrigerator With Drawers Models: WTRD27A, WTRD48A, WTRD60A, WTRD72A

MODEL	WTRD27A-2	WTRD48A-2	WTRD48A-4	WTRD60A-2	WTRD60A-4	WTRD72A-2	WTRD72A-4	WTRD72A-6
EXTERNAL DIMENSIONAL DATA								
Length Overall (inches) Length Overall (mm)	27" 686	48" 1219	48" 1219	60" 1524	60" 1524	72" 1829	72" 1829	72" 1829
Depth Overall (inches) Depth Overall (mm)	29 1/4" 743	29 1/4" 743	29 1/4" 743	29 1/4" 743	29 1/4" 743	29 1/4" 743	29 1/4" 743	29 1/4" 743
Height Overall— (inches) Height Overall— (mm)	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003
Number of doors	-	1	-	1	-	2	1	-
Number of drawers	2	2	4	2	4	2	4	6
Drawer Extension (when opened)	17"	17"	17"	17"	17"	17"	17"	17"
INTERNAL DIMENSIONAL DATA								
NET Capacity (cubic ft.) NET Capacity (Liters)	7.3 207	13.9 394	13.9 394	17.1 484	17.1 484	21.5 609	21.5 609	21.5 609
Internal Length Overall (inches) Internal Length Overall (mm)	23" 584	44" 1118	44" 1118	55 7/8" 1419	55 7/8" 1419	68" 1727	68" 1727	68" 1727
Internal Depth Overall (inches) Internal Depth Overall (mm)	19" 483	19" 483	19" 483	19" 483	19" 483	19" 483	19" 483	19" 483
Internal Height Overall—(inches) Internal Height Overall—(mm)	23" 584	23" 584	23" 584	23" 584	23" 584	23" 584	23" 584	23" 584
Number of shelves	-	2	-	2	-	4	2	-
ELECTRICAL DATA								
Full Load Amperes 115/60/1	4	3.3	3.3	8.2	8.2	8.2	8.2	8.2
REFRIGERATION DATA								
Horsepower	1/6	1/5	1/5	1/4	1/4	1/4	1/4	1/4
WEIGHT DATA								
Gross Weight (Crated lbs)	164	242	242	271	271	330	330	330
Gross Weight (Crated kg)	74	110	110	123	123	150	150	150
	silASS/FIRD	SANITATION		MADE		-	72" OVERALL	WIDTH
		(h)	5 YEAR COMPRESSOR WARRANTY	USA +		_		


27" 39 1/2








WTRD48A-4






72" OVERALL WIDTH

FRONT VIEW

WTRD72A-6

WTRD60A-4




*N/A:: Not available at time of printing.

29 1/4"

Note: Not all markings may apply to all model variations.

END VIEW



BEVERAGE-AIR® CORPORATION

39 1/2"

3779 Champion Blvd. • Winston-Salem, NC 27105 USA • (336) 245-6400 • Fax (336) 245-6453 • (888) 845-9800 • www.beverage-air.com

Specifications are subject to change without prior notice. 06/10 Tundra Specialties

PLAN VIEWS